

D-SW75 SOLID WALL 75

Pre-engineered and 100% factory fabricated, the system provides a unitized and modular feature which allows for quick install and easy relocation. With snap on panels, electrical kits, and an array of finishes. The design possibilities are endless





D-25F

SINGLE GLAZED FINELINE 25

Dela System D-25F i.e. Fineline Single glazed modular system consist of Aluminium section of 25*25*2 mm thick. All sections duly anodized up to 20–25 microns with 6063-T6 grade and required accessories i.e glass to glass aluminium I sections, T section & 90 degree sections & Glass packing to adjust the floor level. Ceiling profile, Floor profile and wall profile are 25 mm visible face and 25 mm wide with 10mm toughen glass & insertion of Thermoplastic gasket to adhere the glass firm & airtight. The sound reduction Value is from 32 to 35 Db

When the architecture of a building promotes lightness and space and the function of the room requires a minimalist partition solution, glazed system Dela D-25F provides the answer. With the glazing held in a perimeter frame profiles 25 x25mm, with no need for gridwork or vertical load-bearing elements, a transparent and open room is created. Aluminium profiles with powder coated or anodised finishes are serving as horizontal and vertical connections to the building structure.

T6 Grade Virgin Aluminium Section Dimensions Width: 25 mm Height: 25 mm

Thickness: 2 mm Gasket: Silicon Based

Glass Connection System: Aluminium/ Clear G2G Seal

Bonding: Glass mounting clear adhesive tape





D-SW100 SOLID WALL 100

Pre-engineered and 100% factory fabricated, the system provides a unitized and modular feature which allows for quick install and easy relocation. With snap on panels, electrical kits, and an array of finishes. The design possibilities are endless