

## D-75T+

### DOUBLE GLAZED TRIMLINE 75



Dela system D-75T+ i.e. Trimline Double glazed modular system consist of Aluminium section of 25\*75\*1.5 mm thick. All sections duly anodized up to 20-25 microns with 6063-T6 grade and required accessories i.e. glass to glass aluminium I sections, T section & 90 degree sections & Glass packing to adjust the floor level. Ceiling profile, Floor profile and wall profile are 25 mm visible face and 60 mm wide with 10mm/12mm toughen glass & insertion of Thermoplastic gasket to adhere the glass firm & airtight. The sound reduction Value is from 45 to 49 Db.

The glass partition Dela D-75T+, is the new benchmark disclosing maximum space transparency combined with unlimited layout flexibility. The two glass panes for the double glazed system are fixed in 75 x 25 mm profiles. Therefore, maximum glass visibility provides an open modern appearance. Good sound insulation & the alternative opportunity for the integration of blinds allow the implementation of an individual, delightful and undisturbed working ambience. Either in offices, conference rooms or training facilities - Dela D-75T+ opens all possibilities to optimize design for the internal space development.

T6 Grade Virgin Aluminium  
Section Dimensions  
Width: 75 mm  
Height: 25 mm  
Thickness: 1.5 mm  
Gasket: Silicon Based  
Glass Connection System: Aluminium/ Clear G2G Seal  
Bonding: Glass mounting clear adhesive tape

